
Diamond Block


Acoustic Wall Tile

filzfelt*




Diamond Block adds a little sparkle. The seemingly straightforward Diamond allows for endless patterning by playing with color combinations and rotating tiles. Combine it with Triangle 60 Block and watch it shine. Available in over ninety colors of 100% Wool Design Felt mounted to a high-performing acoustic substrate with standard or chamfered edges. The modular tiles install easily with heavy-duty construction adhesive while providing sound absorption and all-natural texture.






Exploded Axonometric







2-Color Pattern Code: FF-AK-BLDI-001




3-Color Pattern Code: FF-AK-BLDI-002



4-Color Pattern 1 Code: FF-AK-BLDI-003



4-Color Pattern 2 Code: FF-AK-BLDI-004



4-Color Pattern with Triangle 60 Block Code: FF-AK-BLDI-005

Patterns are shown as suggested installations and may be configured with any combination of FilzFelt colors

Product Diamond Block Content 100% Wool Design Felt + Akustika 10 Substrate (60% post-consumer recycled content) Tile Size 1'-1 7/8" x 2'-0" (35.2 x 61.0 cm) Thickness 1/2 in (13 mm) Thickness Tolerance ±1/16 in (2 mm) Edge Options Standard Chamfered Color Options 1-Color, 2-Color, 3-Color, or 4-Color per wall Design Tool A Design Tool is available to assist in the design of Block tiles. This tool allows patterns to be configured and is available at: dt.filzfelt.com Custom Custom sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Tile Size 1'-1 7/8" x 2'-0" (35.2 x 61.0 cm) Thickness 1/2 in (13 mm) Thickness Tolerance ±1/16 in (2 mm) Edge Options Standard Chamfered Color Options 1-Color, 2-Color, 3-Color, or 4-Color per wall Design Tool A Design Tool is available to assist in the design of Block tiles. This tool allows patterns to be configured and is available at: dt. filzfelt.com Custom Custom sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Thickness Tolerance ±1/16 in (2 mm) Edge Options Standard Chamfered Color Options 1-Color, 2-Color, 3-Color, or 4-Color per wall Design Tool A Design Tool is available to assist in the design of Block tiles. This tool allows patterns to be configured and is available at: dt.filzfelt.com Custom Custom sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Thickness Tolerance ±1/16 in (2 mm) Edge Options Standard Chamfered Color Options 1-Color, 2-Color, 3-Color, or 4-Color per wall Design Tool A Design Tool is available to assist in the design of Block tiles. This tool allows patterns to be configured and is available at: dt.filzfelt.com Custom Custom sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Edge Options Standard Chamfered Color Options 1-Color, 2-Color, 3-Color, or 4-Color per wall Design Tool A Design Tool is available to assist in the design of Block tiles. This tool allows patterns to be configured and is available at: dt.filzfelt.com Custom Custom Sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Color Options 1-Color, 2-Color, 3-Color, or 4-Color per wall Design Tool A Design Tool is available to assist in the design of Block tiles. This tool allows patterns to be configured and is available at: dt.filzfelt.com Custom Custom sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Design Tool A Design Tool is available to assist in the design of Block tiles. This tool allows patterns to be configured and is available at: dt.filzfelt.com Custom Custom sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Waintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Custom Custom Sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted Durability Contract or residential Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Lead Time Made to order and certain lead times will apply Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Installation Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
Tiles may be trimmed to size with a utility knife. Refer to Diamond Block Installation Instructions for complete guidance. Maintenance Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the
surface appearance of the felt. Refer to 100% Wool Design Felt Maintenance + Cleaning for detailed care instructions.
Variation Wool felt is a natural material and color variation and inclusions of natural fiber on the surface are evidence of the 100% natural origin of the material. Product color is only indicative, as it is not possible to assure consistency of color in a natural product due to the natural color of raw wool and absorption of dyes. Color matching cannot be guaranteed on shipments and variation will be more pronounced beyond the normal commercial range.
Environmental 100% Wool Design Felt is 100% biodegradable/compostable and Akustika 10 contains minimum 60% post-consumer recycled content and is 100% recyclable Contains no formaldehyde, 100% VOC free, no chemical irritants, and free of harmful substances 100% Wool Design Felt contributes to LEED© Download Declare Label Living Building Challenge Criteria Compliant Oeko-Tex© Standard 100 Certified Product Class II (100% Wool Design Felt + Akustika 10 Substrate) Meets VOC test limits for the CDPH v1.2 method
Acoustics ASTM C 423: NRC – 0.50, SAA – 0.51
Colorfastness to Light Class 4–5 (40 hours)
Colorfastness to Crocking Class 3–4 (wet), Class 4–5 (dry)
Flammability Test reports available upon request



Standard Colors

100% Wool Design Felt



Akustika 10 Substrate

