

# Index Dimensional

Acoustic Wall Tile



filzfelt •



Index Dimensional in Standard Tile Size

## Index Dimensional has a leg up on sound absorption.

Index Dimensional captures light and shadow in a pattern of repeated and staggered rectangles. Combining one-hundred percent wool felt with natural cork composite backing—two materials known for their acoustic properties—this tile-based wallcovering system provides a dynamic effect on the wall. Choose one color to keep the patterning subtle or play up the dimensionality with up to four colors per wall.

Index Dimensional was designed by Submaterial, a design studio and manufacturer based in Albuquerque, New Mexico.




Index Dimensional in Large Format Tile Size



Index Dimensional in Standard Tile Size




Index Dimensional in Large Format Tile Size




“With many of the surfaces and textures I explore, I believe I am striving to create a balance between simple geometries and complex natural systems. I have always been fascinated by the appearance of randomness, especially when it turns out to be driven by a complex and quite orderly set of rules.”


– David Hamlin with Submaterial, designer of Index Dimensional



**Exploded Axonometric**  
Standard Tile Size Shown




Standard Tile Pattern




**Standard Tile**

Four Distinct Tiles in Standard Pattern



**Large Format Tile Pattern**



**Large Format Tile**

Four Distinct Tiles in Standard Pattern



<b>Product</b>	Index Dimensional
<b>Designer</b>	Submaterial
<b>Content</b>	100% Wool Design Felt + Cork Composite Backing
<b>Tile Sizes</b>	Standard: 2'-0" x 6" (61.0 x 15.2 cm) Large Format: 3'-0" x 1'-0" (91.4 x 30.5 cm)
<b>Thickness</b>	1/4–5/16 in (6–8 mm)
<b>Colors</b>	1-Color to 2-Color per wall
<b>Stocking Program</b>	Stocking Program colors are available in 1-Color option in standard tile size only and ship within three business days from receipt of valid purchase order, subject to inventory availability and payment terms. Standard Colors are made to order and certain lead times will apply.
<b>Trim Options</b>	End-of-Run Trim Outside Corner Trim
<b>Custom</b>	3-Color or more per wall is available and must be quoted Akustika backing available to achieve NRC rating of 0.60
<b>Durability</b>	Contract or residential
<b>Lead Time</b>	With the exception of Stocking Program Colors, tiles are made to order and certain lead times will apply
<b>Installation</b>	Each order includes four distinct tiles that install in a randomized pattern and attach to a wall surface using a heavy-duty wallcovering adhesive. Tiles may be trimmed to size with a utility knife. Refer to Index Dimensional Installation Instructions for complete guidance.
<b>Maintenance</b>	Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt. Refer to Product Maintenance + Cleaning for detailed care instructions.
<b>Variation</b>	Wool felt is a natural material and color variation and inclusions of natural fiber on the surface are evidence of the 100% natural origin of the material. Product color is only indicative, as it is not possible to assure consistency of color in a natural product due to the natural color of raw wool and absorption of dyes. Color matching cannot be guaranteed between individual tiles and expect color variation beyond the normal commercial range.
<b>Environmental</b>	100% Wool Design Felt is 100% biodegradable/compostable and Cork Composite Backing is 93% pre-consumer recycled content Contains no formaldehyde, low VOC, no chemical irritants, and free of harmful substances Cork composite backing is GREENGUARD-certified Contributes to LEED® Download Declare Label Living Building Challenge Criteria Compliant Oeko-Tex® Standard 100 Certified Product Class II (100% Wool Design Felt) Forest Stewardship Council® Certified (Cork Composite Backing) Meets VOC test limits for the CDPH v1.2 method
<b>Acoustics</b>	Standard Cork Backing: ASTM C 423: NRC – 0.20, SAA – 0.21 Custom Akustika Backing: ASTM C 423: NRC – 0.50, SAA – 0.51
<b>Colorfastness to Light</b>	Class 4–5 (40 hours)
<b>Colorfastness to Crocking</b>	Class 3–4 (wet), Class 4–5 (dry)
<b>Flammability</b>	Test reports available upon request

# Colors

## Stocking Program Colors



150 Weiß    160 Beige    170 Asche    175 Graphit    312 Lagune

## Standard Colors

