
## Hanging F

1 11

Space Divider

••••••••

filzfelt



Make Custom Hanging Panels all-your-own.

Love our hanging panels but want to make them your own? Our Custom Hanging Panels are available in thickness from 3mm to 10mm in every hue of our 100% Wool Design Felt and custom designs are limited only by the bolt width. Create a custom pattern or render a logo in these soft, moveable dividers while adding soft acoustic absorption to any space.

The softness, thickness, and density of 100% Wool Design Felt allow these no-nonsense panels to be cut with intricate patterning and hang freely without fraying or additional support. This modern screening system provides varied degrees of privacy and enables flexible space division with visual and acoustic separation to boot.





•••••	
Product	Custom Hanging Panels
Content	100% Wool Design Felt
Maximum Width	3mm + 5mm: 69 in (175 cm) 8mm + 10mm: 60 in (155 cm)
Maximum Length	12'-0" (365.8 cm)
Minimum Cut-out	3mm + 5mm: 3/8 in (1 cm) 8mm + 10mm: 1 in (2.5 cm)
Maximum Cut-out	3 in (7.6 cm)
Track System	FilzFelt's Hanging Panel Track System is available in up to five channels, ceiling or wall mount, stationary or sliding, and Hanging Panels attach with Velcro or grommets for easy hanging and removal for cleaning.
Weighed Rod Pocket	A weighted rod stitched into a felt pocket is available to allow Hanging Panels to hang straight at the bottom and an upcharge will apply. However, as wool felt is a natural material some movement and irregularity may occur.
Durability	Contract or residential
Lead Time	Made to order and certain lead times will apply
Maintenance	Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt. Refer to 100% Wool Design Felt Maintenance + Cleaning for detailed care instructions.
Variation	Wool felt is a natural material and color variation and inclusions of natural fiber on the surface are evidence of the 100% natural origin of the material. Product color is only indicative, as it is not possible to assure consistency of color in a natural product due to the natural color of raw wool and absorption of dyes. Color matching cannot be guaranteed between individual panels and expect color variation beyond the normal commercial range. In addition, variations in temperature and humidity can expand or contract the fibers affecting the size and shape of the felt. Please note that the material dimensions may change up to ±5% due to climate variation.
Environmental	100% Wool Design Felt is 100% biodegradable/compostable Contains no formaldehyde, 100% VOC free, no chemical irritants, and free of harmful substances Contributes to LEED© Download Declare Label Living Building Challenge Criteria Compliant Oeko-Tex© Standard 100 Certified Product Class II Meets VOC test limits for the CDPH v1.2 method
Colorfastness to Light	Class 4–5 (40 hours)
Colorfastness to Crocking	Class 3-4 (wet), Class 4-5 (dry)
Durability + Strength	ASTM 4966 (Martindale Abrasion Tester Method): 5,000 Grade 4, 10,000 Grade 3.5, 20,000 Grade 3.5, 40,000 Grade 3
Flammability	Test reports available upon request
•••••	



## **Standard Colors**

