


Polka 120 is all about what's left behind. Polka 120 Hanging Panels are bold, graphic, and playful. Shifts in circle patterning at a 120 degree offset creates an unexpected, sophistical pattern. Circles are five inches in diameter and break the edge of the panel, allowing a smooth pattern transition between adjacent panels. The softness, thickness, and density of 100% Wool Design Felt allow these no-nonsense panels to be cut with intricate patterning and hang freely without fraying or additional support. This modern screening system provides varied degrees of privacy and enables flexible space division with visual and acoustic separation to boot.

Polka 120 Hanging Panel was designed by Ayse Birsel, an awardwinning designer, author, and lecturer.








"What speaks to me is design as problem solving – how can you solve a problem to transform peoples' lives through design and ultimately improve their lives. This could be a product, this could be an experience, a service, an interface. It could be your life. I use design as a problem solving endeavor."

- Ayse Birsel, designer of Polka 120 Hanging Panel



Product	Polka 120 Hanging Panel
Designer	Ayse Birsel
Content	100% Wool Design Felt
Panel Size	5'-8 3/4" x 8'-0" (174.8 x 243.8 cm)
Thickness	3/16 in (5 mm)
Hanging Options	Velcro or Grommets
Track System	FilzFelt's Hanging Panel Track System is available in up to five channels, ceiling or wall mount, stationary or sliding, and Hanging Panels attach with Velcro or grommets for easy hanging and removal for cleaning. Visit filzfelt.com/hanging-panel-track-system for more information.
Weighted Rod Pocket	A weighted rod stitched into a felt pocket is available to allow Hanging Panels to hang straight at the bottom and an upcharge will apply. However, as wool felt is a natural material some movement and irregularity may occur.
Custom	Custom sizes and patterns are available and must be quoted
Durability	Contract or residential
Lead Time	Made to order and certain lead times will apply
Maintenance	Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt. Refer to 100% Wool Design Felt Maintenance + Cleaning for detailed care instructions.
Variation	Wool felt is a natural material and color variation and inclusions of natural fiber on the surface are evidence of the 100% natural origin of the material. Product color is only indicative, as it is not possible to assure consistency of color in a natural product due to the natural color of raw wool and absorption of dyes. Color matching cannot be guaranteed on shipments and variation will be more pronounced beyond the normal commercial range. In addition, variations in temperature and humidity can expand or contract the fibers affecting the size and shape of the felt. Please note that the material dimensions may change up to ±5% due to climate variation.
Environmental	100% biodegradable/compostable, contains no formaldehyde, 100% VOC free, no chemical irritants, and free of harmful substances Contributes to LEED© Download Declare Label Living Building Challenge Criteria Compliant Oeko-Tex Standard 100 Certified Product Class II Meets VOC test limits for the CDPH v1.2 method
Colorfastness to Light	Class 4-5 (40 hours)
Colorfastness to Crocking	Class 3-4 (wet), Class 4-5 (dry)
Durability + Strength	ASTM 4966 (Martindale Abrasion Tester Method): 5,000 Grade 4, 10,000 Grade 3.5, 20,000 Grade 3.5, 40,000 Grade 3 ASTM D 5034 (Grab Test): 243 lb (avg of warp), 214 lb (avg of weft)
Flammability	Test reports available upon request



Standard Colors

