



**10mm Wool Design Felt**

# Specifications

<b>Name</b>	10mm Wool Design Felt
<b>Content</b>	100% Merino Wool
<b>Country of Origin</b>	Germany
<b>Thickness</b>	10 mm (3/8 in)
<b>Thickness Tolerance</b>	±0.5 mm (±1/5 in)
<b>Width</b>	160 cm (63 in)
<b>Width Tolerance</b>	±4 cm (±1 3/5 in)
<b>Weight</b>	2800 g / m <sup>2</sup> (170 oz / lin yd)
<b>Average Bolt Length</b>	15–17 lin m (17–19 lin yd)
<b>Backing</b>	None
<b>Primary Uses</b>	Architectural Products Hanging Panels Seat Pads Wallcovering
<b>Durability</b>	Light contract or residential (depending on application)
<b>Maintenance</b>	Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt. Refer to 100% Wool Design Felt Maintenance + Cleaning for detailed care instructions.
<b>Environmental</b>	100% biodegradable, contains no formaldehyde, 100% VOC free, no chemical irritants, free of harmful substances Contributes to LEED® v4
<b>Custom</b>	Custom colors and custom fabrication including cutting, lamination, stitching, embroidery and installation services available
<b>Variation</b>	Wool felt is a natural material and color variation and inclusions of natural fiber on the surface are evidence of the 100% natural origin of the material. Product color is only indicative, as it is not possible to assure consistency of color in a natural Product due to the natural color of raw wool and absorption of dyes. Color matching cannot be guaranteed on shipments and variation will be more pronounced beyond the normal commercial range.
<b>Colorfastness to Light</b>	Class 4 (60 hours)
<b>Colorfastness to Crocking</b>	Class 4.5 (wet), Class 4 (dry)
<b>Environmental</b>	Oeko-Tex Standard 100 Certified Product Class II
<b>Flammability</b>	FAR 25.853(a): Pass (60 second vertical burn), Pass (12 second vertical burn)
<b>Standard Color</b>	

