



ARO Array 5

About



Slipping lines form an organic pattern in ARO Array 5, creating a lively visual effect with little transparency. This dynamic pattern adds texture, color, and modulated visibility to any space. The ARO Collection is an Interior Design HiP Performance Wonder award winner.

Hanging Panels offer the soft texture, thickness, and density of 100% Wool Design Felt that allow these no-nonsense panels to hang freely without a backing or additional support. Plus, this nifty nonwoven textile can be cut with intricate patterning without finishing the edges. All this comes together in a modern screening system that provides varying degrees of privacy and enables flexible space division with visual and acoustic separation.



Specifications

| | |
|----------------------------------|---|
| Name | ARO Array 5 |
| Designer | Architecture Research Office |
| Content | 100% Wool Design Felt |
| Felt Thickness | 3/16 in (5 mm) |
| Standard Sizes | Small: 2'-10" x 8'-0" (86.4 x 243.8 cm) Medium: 4'-0" x 8'-0" (121.9 x 243.8 cm) Large: 5'-9" x 8'-0" (175 x 243.8 cm) |
| Hanging Options | Velcro or Grommets |
| Track System | FilzFelt's Hanging Panel Track System is available in up to five channels, ceiling or wall mount, stationary or sliding, and Hanging Panels attach with Velcro or grommets for easy hanging and removal for cleaning. Visit filzfelt.com/hanging-panel-track-system for more information. |
| Weighted Rod Pocket | A weighted rod stitched into a felt pocket is available to allow Hanging Panels to hang straight at the bottom and an upcharge will apply. However, as wool felt is a natural material some movement and irregularity may occur. |
| Durability | Contract or residential |
| Maintenance | Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt. Refer to 100% Wool Design Felt Maintenance + Cleaning for detailed care instructions. |
| Lead Time | Made to order and certain lead times will apply |
| Environmental | 100% biodegradable, contains no formaldehyde, 100% VOC free, no chemical irritants, and free of harmful substances 100% Wool Design Felt contributes to LEED® |
| Custom | Custom sizes + patterns |
| Variation | Wool felt is a natural material and color variation and inclusions of natural fiber on the surface are evidence of the 100% natural origin of the material. Product color is only indicative, as it is not possible to assure consistency of color in a natural product due to the natural color of raw wool and absorption of dyes. Color matching cannot be guaranteed on shipments and variation will be more pronounced beyond the normal commercial range. In addition, variations in temperature and humidity can expand or contract the fibers affecting the size and shape of the felt. Please note that the material dimensions may change up to ±5% due to climate variation. |
| Colorfastness to Light | Class 4-5 (40 hours) |
| Colorfastness to Crocking | Class 3-4 (wet), Class 4-5 (dry) |
| Durability + Strength | ASTM 4966 (Martindale Abrasion Tester Method): 5,000 Grade 4, 10,000 Grade 3.5, 20,000 Grade 3.5, 40,000 Grade 3 ASTM D 5034 (Grab Test): 243 lb (avg of warp), 214 lb (avg of weft) |
| Environmental | Oeko-Tex Standard 100 Certified Product Class II (100% Wool Design Felt) Meets VOC test limits for the CDPH v1.2 method (100% Wool Design Felt) |
| Flammability | Test reports available upon request |

Standard Colors

