


## Index Solid is anything by plain.

Index Solid enables customizable graphic, textural patterning with a single repeated element of 2'-0" x 6" (61 x 15.2 cm) tiles. Over ninety color options allow bold to subtle compositions using the standard tile. Tiles are made with high quality 100% wool felt, natural cork composite backing, and low VOC adhesive. Index Solid can be specified with up to four colors per wall and install easily with heavy-duty wallcovering adhesive.


Index Solid was designed by Submaterial, a design studio and manufacturer based in Albuquerque, New Mexico.






"With many of the surfaces and textures I explore, I believe I am striving to create a balance between simple geometries and complex natural systems. I have always been fascinated by the appearance of randomness, especially when it turns out to be driven by a complex and quite orderly set of rules."


- David Hamlin with Submaterial, designer of Index Solid




**Exploded Axonometric** 




2-Color Pattern 1 Code: FF-SU-INDS-001




**2-Color Pattern 2** Code: FF-SU-INDS-002




3-Color Pattern 1 Code: FF-SU-INDS-003



**3-Color Pattern 2** Code: FF-SU-INDS-004



4-Color Pattern 1 Code: FF-SU-INDS-005



4-Color Pattern 2 Code: FF-SU-INDS-006

Patterns are shown as suggested installations and may be configured with any combination of FilzFelt colors

Product	Index Solid
Designer	Submaterial
Content	100% Wool Design Felt + Cork Composite Backing
Tile Size	2'-0" x 6" (61.0 x 15.2 cm)
•••••	··· <b>··</b> ·······························
Thickness	1/4 in (6 mm)
Color Options	1-Color to 2-Color per wall
Trim Options	End-of-Run Trim Outside Corner Trim
Custom	3-Color or more per wall is available and must be quoted Akustika backing available to achieve NRC rating of 0.50
Durability	Contract or residential
Lead Time	Made to order and certain lead times will apply
Installation	Each order includes equal numbers of tiles per color unless otherwise specified. Tiles attach to a wall surface using a heavy-duty wallcovering adhesive and may be trimmed to size with a utility knife. Refer to Index Solid Installation Instructions for complete guidance.
Maintenance	Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt. Refer to Product Maintenance + Cleaning for detailed care instructions.
Variation	Wool felt is a natural material and color variation and inclusions of natural fiber on the surface are evidence of the 100% natural origin of the material. Since Imprint is constructed with felt strips turned on edge, color variation will be more extreme and is part of the design intent of the product. Shade variation will be very noticeable on the installed product and cannot be more uniform.
Environmental	100% Wool Design Felt is 100% biodegradable/compostable and Cork Composite Backing is 93% pre-consumer recycled content Contains no formaldehyde, low VOC, no chemical irritants, and free of harmful substances Cork composite backing is repurposed FSC Certified cork cutoffs from bottle stopper production Cork composite backing is GREENGUARD-certified Contributes to LEED© Download Declare Label Living Building Challenge Criteria Compliant Oeko-Tex© Standard 100 Certified Product Class II (100% Wool Design Felt) Meets VOC test limits for the CDPH v1.2 method
Acoustics	Standard Cork Backing: ASTM C 423: NRC – 0.20, SAA – 0.21 Custom Akustika Backing: ASTM C 423: NRC – 0.50, SAA – 0.51
Colorfastness to Light	Class 4-5 (40 hours)
Colorfastness to Crocking	Class 3-4 (wet), Class 4-5 (dry)
Flammability	Test reports available upon request



## **Standard Colors**

