




It's hip to be Square (Block).

The shape that has inspired corporate logos and colloquialisms, Square Block may be combined with Rectangle Block and Triangle 90 Block to provide elaborate patterning or stacked to celebrate repetition and regularity. This seemingly simple shape is available in over ninety colors of 100% Wool Design Felt mounted to a high-performing acoustic substrate with standard or chamfered edges. The modular tiles install easily with heavy-duty construction adhesive while providing sound softening oomph and all-natural texture.







Exploded Axonometric




2-Color Pattern Code: FF-AK-BLSQ-001




3-Color Pattern Code: FF-AK-BLSQ-002




4-Color Pattern 1 Code: FF-AK-BLSQ-003



4-Color Pattern 2 Code: FF-AK-BLSQ-004



4-Color Pattern with Triangle 90 Block Code: FF-AK-BLSQ-005



4-Color Pattern with Rectangle A Block, Rectangle B Block, Triangle 90 Block Code: FF-AK-BLRE-005

Patterns are shown as suggested installations and may be configured with any combination of FilzFelt colors

Product	Square Block
Content	100% Wool Design Felt + Akustika 10 Substrate (60% post-consumer recycled content)
Tile Size	1'-0" x 1'-0" (30.5 x 30.5 cm)
Thickness	1/2 in (13 mm)
Thickness Tolerance	±1/16 in (2 mm)
Edge Options	Standard Chamfered
Color Options	1-Color, 2-Color, 3-Color, or 4-Color per wall
Design Tool	A Design Tool is available to assist in the design of Block tiles. This tool allows patterns to be configured and is available at: dt.filzfelt.com
Custom	Custom sizes, shapes, and mounting options are available and must be quoted Tiles in 5/8 in (15 mm) thickness available with a 10% upcharge 5-Color or more per wall is available and must be quoted
Durability	Contract or residential
Lead Time	Made to order and certain lead times will apply
Installation	Install in the pattern as specified and attach to a wall surface using a heavy-duty construction adhesive. Tiles may be trimmed to size with a utility knife. Refer to Square Block Installation Instructions for complete guidance.
Maintenance	Vacuum occasionally to remove general air-borne debris. Should soiling occur, spot clean with mild soap and lukewarm water. Avoid aggressive rubbing as this can continue the felting process and change the surface appearance of the felt. Refer to Product Maintenance + Cleaning for detailed care instructions.
Variation	Wool felt is a natural material and color variation and inclusions of natural fiber on the surface are evidence of the 100% natural origin of the material. Product color is only indicative, as it is not possible to assure consistency of color in a natural product due to the natural color of raw wool and absorption of dyes. Color matching cannot be guaranteed on shipments and variation will be more pronounced beyond the normal commercial range.
Environmental	100% Wool Design Felt is 100% biodegradable/compostable and Akustika 10 contains minimum 60% post-consumer recycled content and is 100% recyclable Contains no formaldehyde, 100% VOC free, no chemical irritants, and free of harmful substances 100% Wool Design Felt and Akustika 10 contribute to LEED© Download Declare Label Living Building Challenge Criteria Compliant Oeko-Tex© Standard 100 Certified Product Class II (100% Wool Design Felt + Akustika 10 Substrate) Meets VOC test limits for the CDPH v1.2 method
Acoustics	ASTM C 423: NRC - 0.50, SAA - 0.51
Colorfastness to Light	Class 4-5 (40 hours)
Colorfastness to Crocking	
	Class 3–4 (wet), Class 4–5 (dry)



Standard Colors

100% Wool Design Felt



Akustika 10 Substrate

